



The Mini Vortex is an essential unit in all labs which require quick mixing of individual test tubes (of varying sizes)

- ◆ Tiny Vortex with the small footprint
- ◆ Brushless DC motor for maintenance free long life
- ◆ Deliver upto 4500 RPM for thorough mixing & quick vortexing
- ◆ Orbital diameter of 4.5 mm
- ◆ Smart and Robust design - press activation with suspension
- ◆ Robust construction with Die cast Al. base and suction cups for stable operation
- ◆ Inbuilt counterbalance - no walking issues
- ◆ Adjustable speed (in iSwix Jr. VT) - range between 2500 to 4500 RPM
- ◆ Can be used inside same hoods / cold rooms

Specifications	iSwix Jr.	iSwix Jr. VT
Max RPM	4500 rpm	
Orbital diameter	4.5 mm	
Motor type	Brushless DC	
Variable speed	No	Yes
Timer setting	No	
Max tube diameter	30 mm	
Max Load Capacity	500 gm	
Press activation	Yes	
Protection class	IP 43	
Dimensions (W X D X H)	100 x 100 x 67 mm	
Weight	0.55 kg	




Maintenance free BLDC Motor



Counter balance for stable operation



Suspension design for longer switch life



Tiny footprint

*OEM request can be entertained. Specifications can be changed without notice for quality improvement.